

# Topper-Seal Foam Technical Data Sheet



## DESCRIPTION

Foam Seal Topper-Seal is a low density industrial PVC foam.

## APPLICATIONS

Foam Seal Topper-Seal is an economical tape for use as a seal between pickup truck caps and body side rail. Topper-Seal remains pliable at temperatures of -20°C to 78°C.

## STORAGE

Product shelf life begins on the date of production as referenced by the lot number. Foam Seal Topper-Seal has a shelf life of 6 months when stored at or below 75°F.

## ADDITIONAL INFORMATION

Foam Seal/Novagard believes that the information provided is a true and accurate description of the typical characteristics of the aforementioned product; however, it is the responsibility of the individual user to thoroughly test the product in their specific application to determine performance, efficacy, and safety.

## PRODUCT SPECIFICATIONS\*

Parameter	Condition	Specification
Gauge (Thickness)	3/16" to 1/4"	+/- 10%
Width (Rolls)	1.5" to < 2.5" wide	+/- 1/16"
Length	< 50' long	0" to +6"
Density (lbs/cu ft)		5.5 – 9.0
Adhesion	Stainless steel	12 oz / in minimum Typical value: >30 oz/in

\* Specifications based on a sample size of three to five. Testing to these specifications may be dependent on the specific application. Specifications are subject to change without notice.

## TYPICAL PROPERTIES

	Test Method	Typical Values
Hardness (Shore "00")	ASTM D2240	25
Force to Compress @ 25 %	ASTM D1667	3.0 psi
Compression Deflection	ASTM D1667	2.0 psi
Water Absorption	ASTM D1056	6 %
Tensile Strength (psi)	ASTM D412	20
Elongation (%) With Adhesive	ASTM D412	110 %
Flammability	MVSS 302	Self-Extinguishing

The information provided in the above table is not intended for use in preparing specifications. Information for reference is intended as a general guideline only. Typical values based on a sample size of three to five and performed within 2 weeks of manufacture.



☎: 618-282-7700

✉: sales@seconrubber.com

🌐: www.seconrubber.com



Document Name: TDS – Topper-Seal Foam v1.5

Effective Date: 03/22/2019