

## BISCO® HT-6240 TRANSPARENT SOLID SILICONE

BISCO® HT-6240 transparent material is a clear solid silicone formulated to be a 40 durometer Shore A material. The unique product clarity designed into the product enables the material to solve aesthetic and design issues within various industrial and handheld device markets. BISCO HT-6240 transparent material is available in various thicknesses and manufactured in roll form to allow fabricators to easily convert the material to the proper dimensions.

### Features and Benefits

- Excellent product clarity provides a solution for aesthetic issues
- Good tear resistance for gasket integrity
- Excellent physical properties means the material will exhibit excellent long term durability
- Tight thickness tolerances for greater reliability

### Applications

- Architectural lighting gaskets
- Handheld device gaskets
- Cell culture plates

Silicone HT-6240 – Typical Physical Properties		
At 1/16" thick		
Property	Test Method	Typical Value
Thickness		0.010" (0.25 mm)
		0.020" (0.50 mm)
		0.031" (0.79 mm)
		0.063" (1.59 mm)
		0.125" (3.18 mm)
Durometer, Pts	ASTM D 2240	40
Tensile, psi	ASTM D 412	1000
Elongation, %	ASTM D 412	450
Tear Resistance, ppi	ASTM D 624	125
Compression Set, % (70 hrs @ 300°F, 25% compression)	ASTM D 395	30
Temperature	SAE J-2236	-80° to 425°F
		(-62° to 218°C)
Color		Transparent

### Material Options

- Material is available with an acrylic or silicone pressure sensitive adhesive applied at greater than 0.031" (0.79mm) thickness

The information contained in this Data Sheet is intended to assist you in designing with Rogers' High Performance Foam Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' High Performance Foam Materials for each application. The Rogers logo, The world runs better with Rogers. and BISCO are licensed trademarks of Rogers Corporation. © 2002, 2003, 2004, 2008 Rogers Corporation, All rights reserved. Printed in U.S.A., 8101-1008-PDF, Publication #180-093

## Standard Thickness Tolerance

Standard Thickness (Inches)	Tolerance (Inches)
≤ 0.014	± 0.002
0.015 – 0.025	+0.003, -0.002
0.026 – 0.040	± 0.004
0.041 – 0.094	± 0.006
0.095 – 0.145	± 0.008

## Width Tolerance

Nominal Width (Inches)	Tolerance (Inches)
0 < T ≤ 3	± 0.063
3 < T ≤ 8	± 0.094
8 < T ≤ 12	± 0.125
12 < T ≤ 18	± 0.188
18 < T ≤ 26	± 0.219
26 < T ≤ 36	± 0.250
>36	± 0.313

### Notes:

1. All metric conversions are approximate.
2. Additional technical information is available.
3. Typical values are a representation of an average value for the population of the property. For specification values contact Rogers Corporation.

The information contained in this Data Sheet is intended to assist you in designing with Rogers' High Performance Foam Materials. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown on the Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers' High Performance Foam Materials for each application. The Rogers logo, The world runs better with Rogers. and BISCO are licensed trademarks of Rogers Corporation. © 2002, 2003, 2004, 2008 Rogers Corporation, All rights reserved. Printed in U.S.A., 8101-1008-PDF, Publication #180-093

Page 2 of 2

The world runs better with Rogers.®



☎: 618-282-7700

✉: sales@seconrubber.com

🌐: www.seconrubber.com